

EZ-Auger - AUG-01

Model AUG-01

A general all purpose Auger designed for the medium duty user for post holes and general hole drilling from 6" w - 24" w to 48" deep.

Features:

- *Uses our multi-purpose back plate which can be reused on a number of our products.. This means you only need to buy the plate once.*
- *The standard assembly includes the back plate, the auger with swivel, hoses and fittings.*
- *Available bit sizes - 6", 9", 12", 14", 18", 24". 18" & 24" tree planting bits are also available.*
- *18" Extensions Available.*
- *Reese Adaptor Available.*
- *Ideal for machines with a lifting capacity of 900# and up (25HP or above recommended).*
- *Recommended for machines equipped with auxiliary hydraulics rated @ 7 GPM to 25 GPM flow with 1500psi - 2500psi pressure rating.*
- *Universal Skid Steer Quick-Tach mounting bracket will fit most Skid Steer models 1994 and newer including Gehl, New Holland, John Deere, Bobcat, Mustang, Case, Thomas & Caterpillar.*
- *Unit ships completely as a kit. Customer to assemble the auger to the back plate, connect hoses and wrap with supplied hose wrap. Hydraulic couplers to mate to your machine are not supplied*
- *Ships via common carrier truck ground freight.*
- *Weight -325 lbs.*

Hydraulic Motor Specifications

- ~ 1 1/2" O.D. Output Shaft with Collar for full 2" O.D.
- ~ Hydraulic Auger Head Weight - 77 lbs., 32 Cubic-Inch Displacement
- ~ 7 RPM per Gallon Speed, 200 RPM @ Maximum Rated Flow
- ~ 25 GPM Rated Maximum Flow, 485 in/lbs Torque per 100 PSI
- ~ 2500 PSI Continuous (Max Pressure), 3000 PSI Peak (Max Pressure)
- ~ Maximum flow and maximum pressure conditions must **not** occur simultaneously.

